


**0836**

Flexible sheet for water-proofing

**Techline 2000**

TCS Geotechnics  
 Technical Civils Solutions Ltd  
 Units 2 & 5 Tetbury Close  
 Martland Park  
 Wigan, WN5 0LA

Factory Reference: 010-TCS

**17****0836-CPR-17/F400**Product Description: **Flexible sheets for waterproofing, Plastic and rubber damp proof sheets – Definitions and characteristics**System or systems of assessment and verification of constancy of performance of the construction product: **System 2+**Notified Body: **British Board of Agreement (BBA) NB 0836****EN13967 2012**

Essential Characteristics	Technical Performance	Bottom Tolerance	Top Tolerance	Unit	Test Standard
Length	15	15	16.5	m	EN 1848-2
Width	4	3.9	4.1	m	EN 1848-2
Mass per unit area (weight)	460	405	515	g/m <sup>2</sup>	EN 1849-2
Tensile MD	>128	-	-	N/50mm <sup>-1</sup>	EN 12311-2
Tensile CD	>117	-	-	N/50mm <sup>-1</sup>	EN 12311-2
Resistance to tearing MD	>263	-	-	N	EN 12310-1
Resistance to tearing CD	>311	-	-	N	EN 12310-1
Resistance to impact	>40	-	-	mm	EN 12691
Water tightness 2 kPa	Pass	-	-	Pass / Fail	EN 1928:2000

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DOP) is issued under the sole responsibility of the manufacturer identified above.

Authorised signatory



Adam Brooksbank (Product Manager)

Company Stamp

**TECHNICAL CIVILS  
 SOLUTIONS LTD  
 CO REG:- 6705826**

**REGISTERED OFFICE ADDRESS**

Units 2 & 5 Tetbury Close  
 Martland Industrial Park  
 Wigan  
 Greater Manchester  
 WN5 0LA

Issue: 001  
 Wigan, 08/17  
 Place and date

