

NETDOWN ANCHOR SYSTEM

PRODUCT DESCRIPTION

Net Down provides protection for exposed membranes, geotextiles and stockpile covers against wind and UV damage.



PROPERTIES	VALUES
PHYSICAL FORM	KNITTED POLYETHYLENE
COLOUR	DARK GREEN
ROLL DIMENSIONS	6m x 100m - 144 KILO PER ROLL
PRE-FABRICATED PANELS	AVAILABLE UP TO 32m WIDE x 300m LONG
ROLL SQUARE METERAGE	600m ²
STATIC PUNCTURE STRENGTH (ASTM D6241-14)	3 350.2N
TENSILE STRENGTH (ASTM D700/D7004M-03)	MD - 859.7N CMD - 1 700N
ELONGATION (ASTM D4595-17)	MD - 56.7% CMD - 44.3%
SHADE RATE	70%
UV RESISTANCE	6000 ppm
TEMPERATURE RESISTANCE (°C)	-15/+40 (RANGE)

The above technical data is the result of laboratory tests with 10% tolerance.

1. TCS Geotechnics is a trading name of Technical Civils Solutions Ltd.
2. TCS Geotechnics Ltd reserves the right to alter product specifications without prior notice.
3. It is the responsibility of all users to satisfy themselves that the above data is current.
4. The above figures are average values obtained from testing to current EN ISO standards.
5. TCS Ltd cannot accept responsibility for the performance of these products as the conditions of use are beyond our control.
6. Installation details are available on request.

REGISTERED OFFICE ADDRESS

Units 2 & 5 Tetbury Close
 Martland Industrial Park
 Wigan
 Greater Manchester
 WN5 0LA

